


DS Series

Motorized Gates

The DS Series motorized swing gate is the ideal choice for handicap access and large material movement to secure areas in facilities such as office buildings, museums, and fitness centers. This motorized gate has a stylish and open appearance that compliments existing architecture and can be fitted with a glass wing or stainless steel tubular arm. Suitable for bi-directional operation and can be paired with a second gate to allow for wider passageways.



DS Series Motorized Gates




FEATURES & BENEFITS

- Compact, powerful drive & control system encased in stainless steel post
- Glass or stainless steel gate/barrier (customization available)
- Gate can be pushed open in case of power failure
- Sensitive impact detection
- Can be configured for single or double gate applications
- Single or bi-directional operation
- Aesthetically pleasing design
- 10 million opening & closing cycles
- ADA compliant

DSI[®]
DESIGNED SECURITY, INC.
A Detex Company

Designed Security, Inc.
302 Detex Drive
New Braunfels, TX 78130
800-272-3555
512-321-4426

www.dsigo.com
dsi@dsigo.com



ELECTRICAL SPECIFICATIONS

Power:	110 - 240 VAC 50/60 Hz
Power consumption:	45W max
Temperature range:	-25° to 45° celcius

MECHANICAL SPECIFICATIONS

Passage width:	Single gate -	max 38.5" with glass wings max 73" with tube barrier
	Dual gate -	max 75" with glass wings max 144" with tube barrier
Opening angle:	Adjustable 0° to 300°	
Opening/closing time:	1.5 - 4 sec (depending on size of barrier)	
Glass barrier height:	39.4" to 70.8"	
Glass barrier material:	3/8" tempered safety glass	
Post height:	39.4"	
Post diameter:	6.26"	
Post material:	304 Stainless steel	

DS Series with glass wing

